



Male plug-in connector - Stackable version - Pitch 3,5mm - Poles 02÷24

GENERAL INFORMATION

pitch:	3,5 mm
housing height:	14,00 mm
housing depth:	2.8 mm
dimensional class:	slow
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	8A
voltage:	160V
impulse voltage:	2.5 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



current:
voltage:
FILE:

-
-
-

-
-
-

-
-
-

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS

BK (STD)	
other colours:	upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PVS02-3,5	N/A	N/A	N/A
03	PVS03-3,5	N/A	N/A	N/A

04	PVS04-3,5	N/A	N/A	N/A
05	PVS05-3,5	N/A	N/A	N/A
06	PVS06-3,5	N/A	N/A	N/A
07	PVS07-3,5	N/A	N/A	N/A
08	PVS08-3,5	N/A	N/A	N/A
09	PVS09-3,5	N/A	N/A	N/A
10	PVS10-3,5	N/A	N/A	N/A
11	PVS11-3,5	N/A	N/A	N/A
12	PVS12-3,5	N/A	N/A	N/A
13	PVS13-3,5	N/A	N/A	N/A
14	PVS14-3,5	N/A	N/A	N/A
15	PVS15-3,5	N/A	N/A	N/A
16	PVS16-3,5	N/A	N/A	N/A
17	PVS17-3,5	N/A	N/A	N/A
18	PVS18-3,5	N/A	N/A	N/A
19	PVS19-3,5	N/A	N/A	N/A
20	PVS20-3,5	N/A	N/A	N/A
21	PVS21-3,5	N/A	N/A	N/A
22	PVS22-3,5	N/A	N/A	N/A
23	PVS23-3,5	N/A	N/A	N/A
24	PVS24-3,5	N/A	N/A	N/A