

POWER RELAY

1 POLE - 3, 5A Medium Load Control (AgNi contacts)

JY Series

■ FEATURES

- Small and good for high density mounting
Mounting space 202mm², height 12.8mm
- UL, CSA recognized
- High sensitivity and low power consumption
Operate power consumption 98mW, rated power consumption 200mW
- Wide operating range
- Plastic sealed type
- Socket mounting type and socket available
- Pin compatible with solid state relays type SJ
- Through hole
- Plastic materials: UL flammability 94V-0
- RoHS compliant.



■ Applications

- Sequencer, FA equipment etc.

■ Part Numbers

[Example] JY - 12 G - K P - UL
 (a) (b) (c) (d) (e) (f)

(a)	Relay type	JY : JY series
(b)	Coil rated voltage	12 : 4.5...48VDC
(c)	Contact rating / material / construction	W : 3A, gold overlay silver nickel, bifurcated contact G : 3A, gold flash silver nickel, single contact R : 3A, silver nickel, single contact HG : 5A, gold flash silver nickel, single contact HR : 5A, silver nickel, single contact
(d)	Enclosure	K : Plastic sealed type
(e)	Terminal type	Nil : PC board mounting type P : Socket mounting type (without JY-W)
(f)	Safety approval	Nil : Without safety standard UL : UL, CSA recognized type

Note: Actual marking omits the hyphen (-) and suffix P and UL

JY Series

■ Specifications

Item			JY - () W	JY - () G	JY - () R	JY - () HG	JY - () HR	Remarks / conditions
	3A type			5A type				
Contact data	Configuration		1a (1 form A (SPST-NO))					
	Construction		Bifurcated (cross bar)	Single				
	Material		Gold overlay silver nickel	Gold flash silver nickel	Silver nickel	Gold flash silver nickel	Silver nickel	
	Resistance		Max. 30 mΩ		Max. 100 mΩ	Max. 30 mΩ	Max. 100 mΩ	Initial (at 6 VDC, 1A)
	Contact rating		3A, 250VAC / 30VDC			5A, 250VAC / 30VDC		
	Max. carrying current		5A					
	Max. switching voltage		250VAC / 150 VDC					
	Max. switching power		750VA, 90W			1,250VA, 150W		
	Max. switching current		3A			5A (socket 3A)		
	Min. switching load *		0.01mA 100 mVDC	10mA 5VDC	100mA 5VDC	10mA 5VDC	100mA 5VDC	
Coil	Rated power consumption		200 mW (48V type: 360 mW)					At 20°C
	Operate power consumption		100 mW (48V type: 170 mW)					At 20°C
	Operating temperature range		-40°C ~ +90°C (48V type: +80 °C)					No frost
Timing data	Operate		Max. 6 ms					At nominal voltage (without diode, without bounce)
	Release		Max. 3 ms					At nominal voltage (without diode, without bounce)
Life	Mechanical		Min. 20 x 10 ⁶ operations					
	Electrical		Min. 100 x 10 ³ operations					Contact rating
Insulation	Insulation resistance		Min. 1,000MΩ at 500VDC					Initial
	Dielectric strength	Open contacts	750VAC, 1 minute					
		Coil contact	2,000VAC, 1 minute					
	Surge strength	Coil to contacts	4,000V (1.2 x 50μs standard wave)					
Other	Vibration resistance	Misoperation	10 to 55 to 10Hz single amplitude 0.75 mm					
		Endurance	10 to 55 to 10Hz single amplitude 0.75 mm					
	Shock resistance	Misoperation	Min. 100m/s ² (11 ± 1ms)					
		Endurance	Min. 1,000m/s ² (6 ± 1ms)					
Dimensions / weight		9.8×20.0×12.8 mm / approx. 5g						
Sealing		Plastic sealed, RTIII						

*: Minimum switching loads mentioned above are reference values. Please perform the confirmation test with actual load before production since reference values may vary according to switching frequencies, environmental conditions and expected reliability levels.

JY Series

■ Coil Data

Coil code	Rated Coil Voltage (VDC)	Coil Resistance +/-10% (Ω)	Must Operate Voltage* (VDC)	Must Release Voltage* (VDC)	Rated Power (mW)
4.5	4.5	100	3.1	0.23	200
5	5	125	3.5	0.25	
6	6	180	4.2	0.3	
9	9	405	6.3	0.45	
12	12	720	8.4	0.6	
18	18	1,620	12.6	0.9	
24	24	2,880	16.8	1.2	360
48	48	6,400	32.6	2.4	

Note: All values in the table are valid for 20°C and zero contact current unless otherwise specified.

Note: Care shall be taken on the heat generated on PC board when maximum carrying current exceeds 10A.

Please perform the confirmation test with actual conditions


*: Specified operated values are valid for pulse wave voltage.

■ Safety Standards


Type	Compliance	Contact Rating		
		JY-()HG-K, JY-()HR-K	JY-()G-K, JY-()R-K	JY-()W-K
UL	UL 508 E56140	5A 250VAC / 30VDC resistive 1/8HP, 125VAC / 250VAC Pilot duty C150, C300	3A 250VAC / 30VDC resistive 1/10HP, 125VAC / 250VAC Pilot duty D150	5A 250VAC / 30VDC resistive 1/8HP, 125VAC /250VAC Pilot duty C300
CSA	C22.2 No. 14 LR 35579			

■ Dimensions

- Dimensions




- Schematics (BOTTOM VIEW)



JY Series

- PC Board Mounting Hole Layout (BOTTOM VIEW)




Tolerance of PC board mounting hole layout: ± 0.1 unless otherwise specified.


(): Reference value

Unit: mm

■ Socket Dimensions



- PC Board Mounting Hole Layout (BOTTOM VIEW)



Tolerance of PC board mounting hole layout: ± 0.1 unless otherwise specified.

(): Reference value

Unit: mm










Note:

1: Socket ordering code: JK-4N










2: Standard IC socket is not recommended. Please use socket "JK-4N"

JY Series

■ Characteristic Data



JY Series



GENERAL INFORMATION

1. ROHS Compliance

- All relays produced by Fujitsu Components are compliant with RoHS directive 2011/65/EU including amendments.
- Use of Cadmium in electrical contacts is exempted as per Annex III of the RoHS directive 2001/65/EU. Please consider expiry date of exemption. Relays with Cadmium containing contacts are not to be used for new designs.
- All relays are lead-free. Please refer to Lead-Free Status Info for older date codes at: <http://www.fujitsu.com/downloads/MICRO/fcai/relays/lead-free-letter.pdf>
- Lead free solder plating on relay terminals is Sn-3.0Ag-0.5Cu, unless otherwise specified. This material has been verified to be compatible with PbSn assembly process.

2. Recommended Lead Free Solder Profile

- Recommended solder for assembly: Sn-3.0Ag-0.5Cu.

Solder by Soldering Iron:

Soldering Iron 30-60W
Temperature: maximum 350-360 °C
Duration: maximum 3 sec.

Flow Solder condition:

Pre-heating: maximum 120 °C
within 90 sec.
Soldering: dip within 5 sec. at
255 °C ± 5 °C solder bath
Relay must be cooled by air immediately
after soldering

We highly recommend that you confirm your actual solder conditions

3. Moisture Sensitivity

- Moisture Sensitivity Level standard is not applicable to electromechanical relays, unless otherwise indicated

4. Tin Whiskers

- Dipped SnAgCu solder is known as presenting a low risk to tin whisker development. No considerable length whisker was found by our in house test.

JY Series

Fujitsu Components International Headquarter Offices

Japan FUJITSU COMPONENT LIMITED Shinagawa Seaside Park Tower 19F, 12-4, Higashi-shinagawa 4-chome, Shinagawa-ku, Tokyo, 140-0002, Japan Tel: (81-3) 3450-1682 Fax: (81-3) 3474-2385 Email: fcl-contact@cs.jp.fujitsu.com Web: www.fujitsu.com/jp/fcl/	Asia Pacific FUJITSU COMPONENTS ASIA, LTD. 102E Pasir Panjang Road #01-01 Citilink Warehouse Complex Singapore 118529 Tel: (65) 6375-8560 Fax: (65) 6273-3021 Email: fcal@sg.fujitsu.com Web: www.fujitsu.com/sg/products/devices/components	Korea FUJITSU COMPONENTS KOREA LIMITED Alpha Tower #403, 645 Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do, 13524 Korea Tel: (82) 31-708-7108 Fax: (82) 31-709-7108 Email: fcal@sg.fujitsu.com www.fujitsu.com/sg/products/devices/components/
North and South America FUJITSU COMPONENTS AMERICA, INC 2290 North First Street, Suite 212 San Jose, CA 95131, USA Tel: (1-408) 745-4900 Fax: (1-408) 745-4970 Email: components@us.fujitsu.com Web: us.fujitsu.com/components	China FUJITSU ELECTRONIC COMPONENTS (SHANGHAI) CO., LTD. Unit 4306, InterContinental Center 100 Yu Tong Road, Shanghai 200070, China Tel: (86-21) 3253 0998 Fax: (86-21) 3253 0997 Email: fcal@sg.fujitsu.com Web: www.fujitsu.com/sg/products/devices/components	
Europe FUJITSU COMPONENTS EUROPE B.V. Diamantlaan 25 2132 WV Hoofddorp Netherlands Tel: (31-23) 5560910 Fax: (31-23) 5560950 Email: info@fceu.fujitsu.com Web: www.fujitsu.com/uk/components	Hong Kong FUJITSU COMPONENTS HONG KONG CO., LTD Unit 506, Inter-Continental Plaza No.94 Granville Road, Tsim Sha Tsui, Kowloon, Hong Kong Tel: (852) 2881-8495 Tex: (852) 2894-9512 Email: fcal@sg.fujitsu.com Web: www.fujitsu.com/sg/products/devices/components/	

©2016 Fujitsu Components Europe B.V. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

The contents, data and information in this datasheet are provided by Fujitsu Component Ltd. as a service only to its user and only for general information purposes.

The use of the contents, data and information provided in this datasheet is at the users' own risk.

Fujitsu has assembled this datasheet with care and will endeavor to keep the contents, data and information correct, accurate, comprehensive, complete and up to date.

Fujitsu Components Europe B.V. and affiliated companies do however not accept any responsibility or liability on their behalf, nor on behalf of its employees, for any loss or damage, direct, indirect or consequential, with respect to this datasheet, its contents, data, and information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof.

Nor do Fujitsu Components Europe B.V. and affiliated companies accept on their behalf, nor on behalf of its employees, any responsibility or liability for any representation or warrant of any kind, express or implied, including warranties of any kind for merchantability or fitness for particular use, with respect to these datasheets, its contents, data, information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Rev. Dec 15th, 2016