

**Flat Telephone cable
Datasheet**



Rated voltage: 48V
Nominal current: 1A

Temperature range min. -20° C
Temperature range max. 70° C

Item No.	Flat Telephone cable 4WAY	Flat Telephone cable 6WAY
B/N	605116	605441
Jacker, outer dimension	PVC 4.8 x 2.4 mm	PVC 6.8 x 2.5 mm
Cross section area	4 x 0.08 sqmm	6 x 0.08 sqmm
strand per conductor	7 x 0.12 mm	7 x 0.12 mm
Conductor material	CCA	CCA
color	BLACK	BLACK
AWG	28AWG	28AWG
Packaging	50 meter spool	50 meter spool
Capacitance	140pF	140pF

Item No.	Flat Telephone cable 8WAY	Flat Telephone cable 10WAY
B/N	605618	605047
Jacker, outer dimension	PVC 8.5 x 2.5 mm	PVC 10.2 x 2.4 mm
Cross section area	8 x 0.08 sqmm	10 x 0.08 sqmm
strand per conductor	7 x 0.12 mm	7 x 0.12 mm
Conductor material	CCA	CCA
color	BLACK	BLACK
AWG	28AWG	28AWG
Packaging	50 meter spool	50 meter spool
Capacitance	140pF	140pF