

Item no.: 262-301  
 Product description: 2-CONDUCTOR TERMINAL BLOCK;  
 LATERAL MARKING; WITH MOUNTING  
 FEET 209-123 FOR TS 35; SIDE-ENTRY;  
 CAGE CLAMP®CONNECTION;  
 HORIZONTAL TYPE



Packing unit 100 2\*50 pieces

Cross section from [mm <sup>2</sup> ]	0,08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	4 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP®CONNECTION
Voltage CSA	300/600 V
Voltage UL	300/600 V
Current UL	20/5 A
Current CSA	20/5 A
Measured voltage EN	630 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	4,15 g
Color	grey
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	23 mm
Height	0,906 in
Width	7 mm
Width	0,276 in
Depth	33,5 mm
Depth	1,32 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0,37 in

	Admission office	Approval no.	Voltage [ V ]	Current [ A ]	Cross section [ mm <sup>2</sup> ]
262-301	BBJ	B/12/696/03	630	32	4
262-301	BV	07436/C0			0,08-4
262-301	CCA	DK96-00357	630	32	4
262-301	CSA	18677-45	300/600	20/5	26-12
262-301	CSM	017956	630	32	4
262-301	DEMKO	120039/03		24	4
262-301	Dep.MaE	CS4590N	300	34	

262-301	DNV	E6998	630	32	4
262-301	FTZU	08Q040/Ex91.0158	600	20/5	12-28
262-301	GL	17295-00HH	630	32	4
262-301	KEMA	94.71117.02	660		0,08-4
262-301	KR	HMB05880-EL002	630	32	32
262-301	LR	91/20242(E3)	750	35	4
262-301	NEMKO	L94015	500		4
262-301	PRS	TE/1219/880590/98	630	32	4
262-301	RMR	99.00007.250	630	32	4
262-301	RosTesT	B09523	630	32	4
262-301	UL	E45172	300/600	20/5	28-12
262-301	VDE	2098ÜG,BI.1	660		4

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected