

PUSHBUTTON SWITCHES

PRODUCT NUMBER 9052.0100



TECHNICAL DATA

Product number	9052.0100
Business unit	Switches, Sensors & Controls
Product Manager	Rettich
Product family	Pushbutton switches
Actuation type	direct
Packing unit	100
Weight	6.500 g
Output	catalogue miniature switch
Switching function	Changeover switch (SPDT momentary)
Material fixed contact	Ag
Contact system	→ Electrical life 25E3
Number of poles	1 - pole
connections	Solder terminal, sealed
Mechanical life endurance	1E5
Rating IEC	4 A 30 V DC 5 A 48 V AC
Contact resistance (new condition)	< 20 mOhm
Insulation resistance (new condition)	> 1000 MOhm
Voltage strength at 250 V	→ small contact distance > 1000 V
Ambient temperature	→ Actuation side min. -25 °C ... +70 °C
Actuators and additional actuators	actuator: CurZn nickel-plated
Housing description	threaded socket: CnZn nickel-plated, hexagonal nuts of nickel-plated CuZn bracket plate: stainless steel base plate: DAP, olivegreen
Connection surface	→ bearing connection silver plated → external connection silver plated
Contact material	Ag
Contact type	lifting contact
Operating force	6.0 N
Miscellaneous	NKK-Nr.: MB-2011 WW 01 / corresponding pushbuttons 9090.03.. see additional parts / stroke 1.8 mm
Type of fastening	central fastening M6 x 0.75

Technical changes reserved. Dimensions are not binding.
Detailed specifications available on request.

Marquardt GmbH · Schloss-Straße 16 · 78604 Rietheim-Weilheim · Germany
Phone: +49 (0) 7424 / 99-0 · Fax: +49 (0) 7424 / 99-2399 · www.marquardt.com · marquardt@marquardt.de