PVxx-7,62-H-P-S euroclamp





Male plug-in connector - with closed ends - Pitch 7,62mm - 02 ÷ 12 poles

GENERAL INFORMATION	
pitch:	7,62 mm
housing height:	7,25 mm
housing depth:	9.2 mm
dimensional class:	slow
wire section:	-
clamp opening size:	
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS	
current:	8A
voltage:	500V
impulse voltage:	6 kV

MECHANICAL CHARACTERISTICS	
-	-

APPROVALS DATA

	-	-	UL 1059
current:	-	-	8A factory / 8A field
voltage:	-	-	300V
FILE:	-	-	E178356

MATERIALS	
housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a

AVAILABLE COLOURS	
GN (STD) GY BK BL RD YL OG	
other colours:	upon request

Copyright ©2020 - euroclamp - http://www.euroclamp.it

terminal: Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PV02-7,62-H-P-S	N/A	N/A	N/A
03	PV03-7,62-H-P-S	N/A	N/A	N/A
04	PV04-7,62-H-P-S	N/A	N/A	N/A
05	PV05-7,62-H-P-S	N/A	N/A	N/A
06	PV06-7,62-H-P-S	N/A	N/A	N/A
07	PV07-7,62-H-P-S	N/A	N/A	N/A
08	PV08-7,62-H-P-S	N/A	N/A	N/A
09	PV09-7,62-H-P-S	N/A	N/A	N/A
10	PV10-7,62-H-P-S	N/A	N/A	N/A
11	PV11-7,62-H-P-S	N/A	N/A	N/A
12	PV12-7,62-H-P-S	N/A	N/A	N/A

Copyright ©2020 - euroclamp - http://www.euroclamp.it