



Connector shell: Steel
 Connector shell plating: Nickel, 60u"
 Connector insulator: PVC UL94V-0 over PBT UL94V-0 contact material and plating: copper , gold plated, >0.7u"
 Threads: UNC4/40
 raw cable insulation resistance is 300V 80°C

| P1 | | P2 |
|--------|-------|--------|
| 1 | ————— | 1 |
| 2 | ————— | 2 |
| 3 | ————— | 3 |
| 4 | ————— | 4 |
| 5 | ————— | 5 |
| 6 | ————— | 6 |
| 7 | ————— | 7 |
| 8 | ————— | 8 |
| 9 | ————— | 9 |
| SHIELD | ————— | SHIELD |

| No. | DESCRIPTION | Q'TY |
|-----|--|------|
| 5 | BLACK PVC TUBE Ø3.0*22mm | 2 |
| 5 | ALUMINUM FOIL 33*65mm | 2 |
| | MOLDED PE COLOR TRANSPARENT | |
| | MOLDED PVC BEIGE | |
| 4 | NON-UL 9C 2BAWG, ALUM-MYLAR FOIL SHIELDING WITH DRAIN WIRE, OD 5.0mm, JACKET BEIGE | L |
| 3 | MOLDED THUMBSCREW #4-40, LENGTH 46.5mm, BEIGE | 4 |
| 2 | DB9 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR | 1 |
| 1 | DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR | 1 |

Cable Length
 Unless Other Spec.
 Tolerances:
 0 ~0.2M ±0.01M
 0.21~1.0M ±0.02M
 1.1 ~1.5M ±0.025M
 1.51~2.1M ±0.03M
 2.1M ↑ ±0.04M