



Model: LP103454		Overcharge Detection Voltage(V)	4.28±0.05
Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) ※Single cell capacity (单体电芯容量)	1900	Overdischarge Detection Voltage(V) 过放保护电压 (V)	3.0±0.1
Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) ※Single cell capacity (单体电芯容量)	2000	Limited to Max loading current 仅用于最大的负载电流 客户要求最大的负载电流 peak value (A) constant (A) 峰值 2 (A) 持续 1 (A)	
Nominal Voltage 标称电压 (V)	3.7	Customer required Max loading current 客户要求最大的负载电流 peak value (A) constant (A) 峰值 (A) 持续 (A)	
Internal impedance 内阻 (≅) (mΩ, AC 1KHz)	200	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)	
Charge Temp. 充电温度 (°C)	0~45	Battery protection Related Value: (相关的电池保护值)	
Discharge Temp. 放电温度 (°C)	-20~60		
Humidity (湿度)	65±20%		

		Drawn:	zhuhaoran	Revise No.:	E4-2009
Title	LP103454+PCM/LD/	Checked 1:	Shannon	Projection:	
File NO.	A09150	Checked 2:		Page:	1/1
		Approved:		Scale:	1 : 1.5
		Draw Date:	2014/02/06	Unit:	mm

Remark(备注):
 1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. Rohs compliant(严格按照ROHS要求生产).