



dLAN Wireless extender

Technical details

Standards	<ul style="list-style-type: none"> ▪ Wireless specification IEEE 802.11b,g ▪ HomePlug standard 1.0 Turbo ▪ Ethernet standard IEEE 802.3/x/u, Auto MDI /MDI-X
Protocols	CSMA/CD
Data transfer rate	<ul style="list-style-type: none"> ▪ 85 Mbps over powerline ▪ 54 Mbps via wireless
Transfer method	Asynchronous
Modulation	<ul style="list-style-type: none"> ▪ OFDM-84 carrier (orthogonal frequency division multiplexing) via powerline ▪ DSSS (Direct Sequence Spread Spectrum) via wireless – 802.11b/OFDM (orthogonal frequency division multiplexing) – 802.11g
Range	<ul style="list-style-type: none"> ▪ 200m via powerline ▪ Up to 300m via wireless
Security	<ul style="list-style-type: none"> ▪ DES_{pro} encryption via powerline ▪ WEP, WPA, WPA2 via wireless
LEDs	4 LEDs: <ul style="list-style-type: none"> ▪ Power ▪ dLAN Link/Act ▪ WLAN On/Act ▪ ETH Link/Act
LAN connections	dLAN: EURO power plug WLAN: Coaxial connector with removable, rotatable 2.4 GHz antenna Ethernet: RJ45
Power consumption	6,5 W
Power supply	Integrated supply from plug socket Rated voltage: 100 – 240 V AC Rated current: 0,11 A Rated frequency: 50/60 Hz
Temperature	Storage: -25 °C – 70 °C Operation: 0 °C – 40 °C
Dimensions	95 x 70 x 47mm (height x width x depth)
Weight	432 g
Environment	10 – 90% humidity (non-condensing)
Operating systems	Windows [®] XP, Windows [®] Vista, Linux [®] , Mac OS-X, and others
Approvals	CE compliant in accordance with all technical requirements for all EU countries and Switzerland: EN 60950-1 :2001, EN 55022 :1998+A1 :2000 + A2 :2003 (Class B) EN 55024 :1998+A1 :2001+A2 :2003, EN 61000-3-2 :2000, EN 61000-3-3 :1995+A1 :2001 EN 300 328 V1.6.1, EN 301 489-1 V1.4.1, EN 301 489-17 V1.2.1
Modes	<ul style="list-style-type: none"> ▪ Access point with WEP, WPA, WPA2 ▪ Client (bridging mode) with WEP
Other	HTML configuration interface



dLAN Wireless extender

Sales information

Article number	01207 (DE/AT/CH/BE/IT/NL/ES), 01209 (FR), 01208 (UK)
EAN code	4250059612075 (DE/AT/CH/BE/IT/NL/ES), 4250059612099 (FR), 4250059612082 (UK)
Warranty	3 years
Service & Support	Telephone and e-mail support. Telephone numbers and e-mail addresses are available on the support flyer enclosed with the product, and on the devolo web site.
Design	Wall plug plastic housing (large)
Weight	432 g
Packaging size	188,5 x 231 x 78,5 mm (height x width x depth)
Accessories	<ul style="list-style-type: none">▪ Documentation: printed installation guide▪ CD-ROM: PDF manual, configuration software for Windows® XP, Windows® Vista, Linux®, Mac OS-X

WEEE Zusatzinformationen

Weight WEEE	192,2 g
Paper (Green Dot)	186 g
Plastic (Green Dot)	6 g
Other (Green Dot)	0,2 g