



NOTES:

MATERIAL

- 1. Insulator Material: PBT+30%GF(UL94V-0), Black
- 2. Contact Material : Brass
- ⑤ 3. Contact Plating : Gold Flash or Tin plated

ELECTRICAL

- 1. Current Rating : 3.0Amps/contact max
- ⑥ 2. Withstand Continuous Voltage: 1000V AC/DC
- 3. Contact Resistance : 20mΩ/contact max
- 4. Insulation Resistance: 1000MΩ min at Voltage=100V

ENVIRONMENTAL

- 1. Operation Temperature: -40°C to +105°C
- 2. Mechanical life cycle: min.200

Order code: A-BL254-DG-xxxD

Contact plating No. of poles
 G: Gold flash
 ⑤ Z: Tin

RoHS compliant
 Unit: mm

Scale	Free	⑥	Update	12.12.2013	Amy		Date	Name	Customer-No.
TOLERANCE		⑤	Add Tin plating	09.04.2013	Amy	Drawn	30.11.2007	N.Schulz	ASSMANN WSW-No. A-BL254-DG-xxxD
X.	±0.50	④	Change of Plant	27.09.2012	Amy	Approved	12.12.2013	Amy	
X.XX	±0.30	③	Add dimension	01.12.2010	Rale				
X.XXX	±0.20	②	Modify drawing	27.07.2009	Dean				Drawing-No.
DIM	TOL	①	Drawn	30.11.2007	N.Schulz				ASS 1034 CO
Angle	±5°	Id.	Modification	Date	Name			Replace	rev06
									SHEET



ASS 1034 CO rev06

Replace SHEET