

Data sheet

235-401/331-000

1-CONDUCTOR PCB TERMINAL BLOCK 2 SOLDER PINS / POLE
PIN SPACING 5/5.08 MM / 0.2 IN WITH PUSH BUTTONS SIDE-ENTRY



Technical data

Package size 800 8*100 pieces.

Pin spacing from	5 mm
Pin spacing up to	5.08 mm
Pin spacing from	0.197 in
Pin spacing up to	0.2 in
pole count	1
Cross section from [mm ²]	0.5 mm ²
Cross section to [mm ²]	1.5 mm ²
Cross section from [AWG]	20 AWG
Cross section to [AWG]	16 AWG
Wiring method	e
Voltage UL	300 V
Voltage CSA	300 V
Current UL	10 A
Current CSA	10 A
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	10 A
Measured voltage EN	500 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	10 A
Weight	0.752 g

Data sheet**235-401/331-000****1-CONDUCTOR PCB TERMINAL BLOCK 2 SOLDER PINS / POLE
PIN SPACING 5/5.08 MM / 0.2 IN WITH PUSH BOTTONS SIDE-ENTRY**

Color	grey
Wiring type	Side-entry
No. of connection Points	1
No. of potentials	1
Height	15.5 mm
Height	0.61 in
Width	5 mm
Width	0.197 in
Depth	12.5 mm
Depth	0.492 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in

Data sheet

235-401/331-000

**1-CONDUCTOR PCB TERMINAL BLOCK 2 SOLDER PINS / POLE
PIN SPACING 5/5.08 MM / 0.2 IN WITH PUSH BOTTONS SIDE-ENTRY**

Approval	Voltage	Current	Approval number	Notes
BV	250	10	11915/A0	
CCA	500/250	10	DK96-00649	
CSA	300	10	18677-34	
CSM	500/250	10	017956	
DEMKO	250	10	120168/02	
DNV	500/250	10	E6998	
KEMA	400	10	97,1394.02	
NEMKO	300	10	L87192	
RMR	500/250	10	99.00007.250	
RosTesT	500/250	10	B09523	
UL	300	10	E45172	

Data sheet

235-401/331-000

**1-CONDUCTOR PCB TERMINAL BLOCK 2 SOLDER PINS / POLE
PIN SPACING 5/5.08 MM / 0.2 IN WITH PUSH BOTTONS SIDE-ENTRY**

Accessories


Item number

END PLATE SNAP FIT TYPE	235-100
SCREWDRIVER Type 1, bar (2,5 x 0,4) mm	210-119
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 1, bar (2,5 x 0,4) mm	210-619
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5 MM	249-161
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5 MM	249-162
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5 MM	249-163
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5 MM	249-164
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5 MM	249-160/237-106
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5.08 MM	249-166
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5.08 MM	249-167
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5.08 MM	249-168
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5.08 MM	249-169
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5.08 MM	249-165/237-126
SPACER FOR DOUBLING THE PIN SPACING	235-701
STAND OFF FOR INCREASING AIR END CREEPAGE DISTANCE	235-702

Data sheet

235-401/331-000

1-CONDUCTOR PCB TERMINAL BLOCK 2 SOLDER PINS / POLE
PIN SPACING 5/5.08 MM / 0.2 IN WITH PUSH BUTTONS SIDE-ENTRY



Data sheet

235-401/331-000

**1-CONDUCTOR PCB TERMINAL BLOCK 2 SOLDER PINS / POLE
PIN SPACING 5/5.08 MM / 0.2 IN WITH PUSH BOTTONS SIDE-ENTRY**

Diameter of drilled hole: 1^{+0,1} mm