

Data sheet

289-555

**INTERFACE MODULE WITH SUB MINIATURE D-FEMALE CONNECTOR
CARRIER RAIL DIN 35 CAGE CLAMP CONNECTION FOR MATING CONNECTORS
WITH SOLDER CONNECTION**



Technical data

Package size 1 piece.

Operating voltage	AC / DC 125 V
Nominal current (A)	2 A
Connector contact	plating. 0.5-0.8 μ m Au over 2 μ m Ni
Contact resistance	\leq 10 mOhm
Performance level	2 / 200 mating cycles
Nominal voltage acc. to VDE 0110/1.89	125 V / 0,8 kV / 2
Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Weight	46.8 g
Color	No criteria available
Height	34 mm
Height	1.339 in
Width	85 mm
Width	3.346 in
Depth	38 mm
Depth	1.5 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in

Data sheet

289-555

INTERFACE MODULE WITH SUB MINIATURE D-FEMALE CONNECTOR CARRIER RAIL DIN 35 CAGE CLAMP CONNECTION FOR MATING CONNECTORS WITH SOLDER CONNECTION

Accessories

Item number

ALUMINIUM CARRIER RAIL 35 X 7.5 MM, 1.5 MM / 0.059 IN THICK	210-196
COPPER CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-198
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-114
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-197
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-506
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-508
STEEL CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-118
STEEL CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-548
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-112
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-113
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-162
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-229
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-504
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-505

Data sheet

289-555

**INTERFACE MODULE WITH SUB MINIATURE D-FEMALE CONNECTOR
CARRIER RAIL DIN 35 CAGE CLAMP CONNECTION FOR MATING CONNECTORS
WITH SOLDER CONNECTION**

